

GLADSTONE



QINGDAO GLADSTONE INDUSTRIAL CO.,LTD

T:0086-532-86760839

M:0086-15064837919

A:Room 504, No.1166 Li Jiang xi road, Rio Carnival ,Qingdao Shandong China.

E:info@gladstonetire.com export@gladstonetire.com

OTR TYRE 工程机械轮胎系列



E-3/L-3



E3/L3



E3/L3



E-3/L-3

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
7.50-16	8	810	205	5.50E	650	250	E3/L3
8.25-16	10	885	235	6.50H	970	280	E3/L3
9.00-16	10	834	225	6.50H	1080	310	E3/L3
9.00-20	14	1018	259	7.0	2500	810	E3/L3
10.00-16	12	910	275	W8L	1090	310	E3/L3
11.00-16	12	970	315	W10L	1060	310	E3/L3
12.00-16	12	884	244	8.5	1100	320	E3/L3
14/90-16	12	896	215	8.5H	1245	290	E3/L3
16/70-16	14	870	260	8.5H	1055	390	E3/L3
16/90-16	14	870	260	8.5H	1055	390	E3/L3
16/70-20	16	1075	410	13.00	3375	350	E3/L3
16/70-24	16	1175	410	13.00	3350	450	E3/L3
205/70-16	14	1075	410	8.5H	2850	350	E3/L3
23.5-16	14	1075	410	8.5H	2850	350	E3/L3
17.5-25	16	1350	445	14.00/1.5	7300	475	E3/L3
20.5-25	20	1490	520	17.00/2.0	9500	450	E3/L3
23.5-25	24	1615	595	19.50/2.5	12500	475	E3/L3
26.5-25	28	1750	675	22.00/3.0	15500	475	E3/L3
29.5-25	28	1875	750	25.00/3.5	17500	425	E3/L3
13.00-24	12	1350	350	10.00	5600	450	E3/L3
14.00-24	16	1370	375	10.00	7300	550	E3/L3
14.00-25	24	1370	375	10.00/1.5	9500	850	E3/L3
16.00-24	28	1495	430	11.25/2.0	11500	750	E3/L3
16.00-25	28	1495	430	11.25/2.0	11500	750	E3/L3
18.00-24	32	1615	500	13.00/25	15000	750	E3/L3
18.00-25	32	1615	500	13.00/25	15000	750	E3/L3

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
7.5-16	6	810	205	5.50E	650	250	E3/L3
8.25-16	14	885	235	6.50H	970	280	E3/L3
20.5/70-16	14	1075	410	8.50H	2850	350	E3/L3

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
20.5/70-16	14	1075	410	8.5H	2850	350	E3/L3
23.5- 16	14	1075	410	8.5H	2850	350	E3/L3
16/70-20	16	1075	410	13.00	3375	350	E3/L3
16/70-24	16	1175	410	13.00	3350	450	E3/L3
15.5- 25	16	1275	395	12.00/1.3	6750	525	E3/L3
17.5- 25	16	1350	445	14.00/1.5	7300	457	E3/L3
20.5- 25	20	1490	520	17.00/2.0	9500	450	E3/L3
23.5- 25	24	1614	595	19.50/2.5	12500	475	E3/L3
26.5- 25	28	1750	675	22.00/3.0	15500	475	E3/L3
29.5- 25	28	1875	750	25.00/3.5	17500	475	E3/L3

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
23.1-26	10	1581	587	DW20A	2900	140	R3



E3/L3



E3/L3



R3

INDUSTRIAL TYRE 工业轮胎系列



R4

R4-1

R4-2

R4-3



SKS-1



SKS-2



SKS-3



SKS-4



L5-1



L5-2



L5-1



L5-2

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
10.5/80-18	10	912	274	9.0	1630	350	R4
12.5/80-18	12	1001	350	9.0	2625	370	R4



R4

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
10-16.5	10	779	261	8.25	2170	520	SKS-1
12-16.5	12	790	300	9.75	2900	550	SKS-1
14-17.5	14	922	351	10.5	3875	550	SKS-1
15-19.5	14	1029	391	11.75	4565	485	SKS-1



SKS-1

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
16.9-28	12	1435	430	15	3450	260	R4-1



R4-1

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
10-16.5	12	792	265	8.25	2170	520	SKS-2
12-16.5	14	826	300	9.75	2865	550	SKS-2



SKS-2

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
17.5L-24	10	1241	445	15	1900	190	R4-2
19.5L-24	12	1314	495	17	3455	230	R4-2
21L-24	14	1402	533	18	3075	250	R4-2



R4-2

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
10-16.5	12	792	265	8.25	2170	520	SKS-3
12-16.5	14	826	300	9.75	2865	550	SKS-3



SKS-3

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
16.9-24	12	1236	429	15	3250	260	R4-3



R4-3

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
10-16.5	12	792	265	8.25	2170	520	SKS-4
12-16.5	14	826	300	9.75	2865	550	SKS-4



SKS-4

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
10-16.5	12	792	265	8.25	2170	520	L5-1
12-16.5	14	826	300	9.75	2865	550	L5-1



L5-1

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
10-16.5	12	792	265	8.25	2170	520	L5-2
12-16.5	14	826	300	9.75	2865	550	L5-2



L5-2

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
19.5L-24	12	1340	495	17	3455	230	L5-1



L5-1

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
19.5L-24	12	1340	495	17	3455	230	L5-2



L5-2

FORKLIFT TRUCK TYRE

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)
5.00-8TT	10	470	137	3.50D	1295	900
6.00-9TT	10	540	160	4.00E	1795	850
6.50-10T	10	590	175	5.00F	1965	775
7.00-12TT	14	683	192	5.00S	2670	1000
7.00-15TT	14	750	200	5.50F	3100	945
7.50-15TT	14	808	215	6.00G	3375	925
8.20-15TT	14	847	236	6.50H	3830	830
18*7-8TT	14	465	173	4.33R	1840	900
21*8-9TT	14	535	200	6.00E	2300	900
23*10-12TT	12	632	200	8.00	3290	700
23*9-10TT	16	584	229	7.00	2300	800
250-15TT	16	735	250	7.5	4350	850
27*10-12TT	14	690	250	8.00G	3620	750
28*9-15TT	14	710	220	7.00	3285	800
300-15TT	20	840	300	8.00	6825	900



SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
13.00-24	12	1278	333	8.00TG	5600	450	G2/L2
14.00-24	16	1348	362	8.00TG	7300	550	G2/L2
17.5-25	16	1350	445	14.00/1.5	7300	475	G2/L2



G2/L2

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
400/60-15.5	14	874	400	13.00	2900	360	I3
500/60-22.5	16	1172	500	16.00	4875	320	I3
550/45-22.5	16	1070	550	16.00	4375	280	I3
550/60-22.5	16	1238	550	16.00	5450	280	I3
600/55-22.5	16	1238	600	20.00	5800	280	I3



I3

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
11L-15TL	10	813	279	8.00	1060	360	F3
11L-16TL	12	838	279	8.00	1250	420	F3



F3

AGRICULTURAL TYRE 农业轮胎系列

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
6.00-12	6	650	145	4.50E	405	250	PR-1
6.00-14	6	675	145	4.50E	420	260	PR-1
6.50-16	6	830	165	5.00F	585	250	PR-1
7.50-16	8	890	195	5.50F	750	300	PR-1
8.3-20	8	950	210	W7	970	270	PR-1
8.3-24	8	1050	210	W7	1135	270	PR-1
9.00-20	8	950	240	W8	955	280	PR-1
9.50-20	8	950	240	W8	955	280	PR-1
9.50-24	8	1150	240	W8	1315	240	PR-1
11-32	10	1480	305	DW10	1080	160	PR-1
11.2-24	10	1205	285	W10	1465	210	PR-1
12.4-24	10	1260	315	W11	1510	230	PR-1
12.4-28	10	1315	315	W11	1785	200	PR-1
13.6-38	10	1710	345	W11	2675	230	PR-1
14.9-24	10	1265	378	W13	1760	180	PR-1
14.9-26	10	1400	378	W12	1820	180	PR-1
14.9-30	10	1560	398	W13	2190	230	PR-1
16.9-34	10	1670	430	W15	2605	200	PR-1



PR-1

SIZE	PR	Overall Diameter (mm)	Section Width (mm)	Rim	Max.load (kgs)	Relative Pressure (kpa)	Pattern
5.00-12	8	590	145	4.00E	280	200	R1-1
5.50-17	8	735	150	4.00E	400	280	R1-1
6.00-12	8	640	165	4.50E	405	250	R1-1
6.00-14	8	690	165	4.50E	450	250	R1-1
6.00-16	8	745	165	4.50E/5.00F	495	250	R1-1
6.50-16	8	760	170	4.50E	630	340	R1-1
7.50-16	8	810	205	5.00F/5.00F	650	210	R1-1
7.50-20	8	910	205	5.00F	1020	370	R1-1
8.0-20	8	950	210	W7	880	250	R1-1
8.3-24	8	995	210	W7	810	240	R1-1
8.5-20	8	895	210	W7	705	230	R1-1
9.5-20	8	950	240	W8	955	280	R1-1
9.5-24	8	1050	240	W8	1110	280	R1-1
11-32	10	1360	305	W10	1000	140	R1-1
11-38	10	1540	305	W10	1545	160	R1-1
11.2-24	10	1105	285	W10/W9	1045	180	R1-1
11.2-28	10	1205	285	W10	1305	240	R1-1
11.2-38	10	1459	285	10.00	1055	120	R1-1
12-38	10	1575	330	DW11	1800	220	R1-1
12.4-24	10	1160	315	W11	1415	230	R1-2
12.4-28	10	1205	315	W10/W9	1115	180	R1-2
13.6-24	10	1210	345	W12	1790	250	R1-3
13.6-28	10	1310	345	W12	1910	250	R1-3
13.6-38	10	1565	345	W12	2215	250	R1-3
14.9-24	10	1265	378	W13	1990	230	R1-3
14.9-28	10	1365	378	W13	2120	230	R1-3
14.9-30	10	1415	378	W13	2190	230	R1-3
15-24	10	1310	400	W14	2800	280	R1-2
15.5/80-24	10	1240	394	W13	2900	300	R1-3
15.5-38	10	1570	395	W14L	2320	230	R1-3
16.9-24	10	1335	429	W15L	1960	200	R1-2
16.9-28	10	1435	430	W15L	2575	240	R1-2
16.9-30	12	1485	430	W15L	2245	170	R1-2
16.9-34	12	1585	430	W15L	2605	200	R1-2
18.4-26	12	1450	467	DW16	2645	180	R1-2
18.4-30	12	1550	485	DW16A	2815	180	R1-2
18.4-34	12	1650	465	W16L	2990	180	R1-2
18.4-38	12	1755	467	W16L	3165	180	R1-2
20.8-38	12	1835	528	W18L	3475	160	R1-2
23.1-26	12	1605	587	DW20	3250	170	R1-2



R1-1



R1-2



R1-3